

PS45 - Premium Clip-On Ear Protector

Collection: Hearing Protection

Range: Hearing Protection

Materials: ABS, PU, PVC, Polyoxymethylene, Stainless Steel

Product information

Premium Clip-On Ear Muff using the same cup as our PS46 Premium Ear Muff. Easy to clip-on and compatible with Endurance, Height Endurance and Expertbase safety helmets. Warning: attenuation performances vary depending on the helmet style they are used with.

Standards

EN 352-3 (SNR 25dB)

Hearing Protection


Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Features

- Easy to clip-on
- Adjustable dual pin system provides multiple positioning for better fit
- Stand-off position for intermittent use
- Suitable for most standard hard hats
- CE certified
- CE-CAT III
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines



PS45 - Premium Clip-On Ear Protector
Commodity Code: 6506101000

Test House

SATRA Technology Europe Ltd (Notified Body No.: 2777)
 Bracetown Business Park
 D15 YN2P, Ireland
 Cert No: 277_13982_01_E00_00

CARTON DIMENSIONS/WEIGHT

| Item | Colour | Len | Wid | Hgt | Weight (Kg) | Cubic (m ³) | EAN13 | DUN14 |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| PS45GRR | Grey | 76.0 | 49.0 | 49.0 | 0.3720 | 0.1825 | 5036108326082 | 15036108814869 |

PERFORMANCES - SOUND ATTENUATION - EN 352-3:2002

| PS45 | | | | | | | | | |
|--|-------------------------|-----------|------------|------------|------------|-------------|-------------|-------------|-------------|
| A | Frequency (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
| B | Mean Attenuation (dB) | 10.5 | 11 | 20.6 | 27.9 | 38.0 | 33.4 | 34.1 | 30.3 |
| C | Standard Deviation (dB) | 6.7 | 5.3 | 5.7 | 5.0 | 4.8 | 4.2 | 4.4 | 6.6 |
| D | Assumed Protection (dB) | 3.8 | 5.7 | 14.9 | 22.8 | 33.2 | 29.1 | 29.7 | 23.7 |
| SNR 25dB H:29dB M: 24dB L: 14dB | | | | | | | | | |

PS45GRR